

AVAILABLE COLORS

- ☒ Extra Warm White 2700K
- ☒ Warm White 3000K
- ☒ Cool White 3500K
- ☒ Natural White 4000K
- ☒ Daylight White 5000k
- ☒ Cold White 6500K
- ☐ Custom

ORDERING CHART

LEDSCAPE FLEX OPTIC STRIP IP65/IP67

LEDscape LED OPTICS LED strip (IP67) is a high quality, flexible LED strips with a unique, diffuse co-extrusion technology that allows horizontal and vertical bending. The combination of high quality and exceptional flexibility, allows for an endless range of indoor and outdoor applications. The LEDscape offers a pre-assembled mirror welded connector for instant waterproof IP67 usage.

PRODUCT HIGHLIGHTS

- **BINNING:** $\pm 50K$
- **CRI:** >90
- **EXPECTED LIFETIME:** L70 $> 50,000$ hours
- **OPERATING TEMP:** 22°F – 131°F (-30°C – 55°C)
- **RATING:** UL
- **OPERATING WATTAGE:** 5.49 watt/foot
- **CORD LENGTH EXPECTED:** 3 ft
- **OPERATING VOLTAGE:** 24V, constant voltage
- **WARRANTY:** 5 year
- **FEATURES:** Dimmable, Plug & Play, Assorted colors, Accessories available, Effective heat dissipation, Excellent lumen/watt ratio, very flexible, custom output, custom colors.

CHARACTERISTICS

Power	Asymmetric	Length Inc. ¹	Max Run Length ²	Dimming
FLEX-O 5.49 w/ft	660 lm/ft	6.56 in	16.4 ft	Low Voltage/ 0-10V
FLEX-OS 5.49 w/ft	490 lm/ft	1.09 in		

Notes:

1. **Length Increments:** Refers to the Strip's cuttable segments.

2. **Max Run Length:** Refers to the Strip's total run lengths from the connector to the end, including interconnected lengths.

Example: If ordering 30 FT, you will receive 2 EA 15 FT Lengths.

Lumen calculated at 4000K. Circuits with LEDscape product must have surge protection to qualify for 5 year warranty. LEDscape reserves the right to modify the information above without notice.


Example: 10-FLEX-O-20-27-AC

Length	LED Stock Code	Series		Beam Angle		Color		Environment		Mounting	
16 ft NOTE: Refer to Max Run lengths. If total exceeds, you will receive multiple pieces. Example: 32 ft = (2) 16 ft	FLEX LED Strip (Outdoor IP65/IP67)	0	Optic 660lm/ft	20	20°	27	2700k	67	IP67	AC	Aluminum Channel
		OS	Optic 490lm/ft	30	30°	30	3000k			ADJ	Adjustable Channel
				45	45°	35	3500k			SC	Saddle Clip
				60	60°	40	4000k				
				2045	20° x 45°	50	5000k				
						65	6500k				
						CU	Custom Color				

Notes:

Product sold PER FOOT. Ships with factory IP67 Connection and end cap. Stock code may differ from UL/ETL certification, consult factory if required.

OPTIC CONNECTOR & MOUNTING




S67 STRAIGHT CONNECTOR SET IP67

Part #: Flex-O-Conn-S67

Cord length: 3 ft

Dimensions: 0.31 L x 0.78 W x 0.43 H inches



JMP67 JUMPERSET IP67


Part #: Flex-O-Jmp67

Cord length: 6 in

Part #: Flex-O-Jmp67-XX

XX: Select Length (inches)

Dimensions: 0.31 L x 0.78 W x 0.43 H inches



EC67 END CAP IP67

Part #: Flex-O-EC67

Dimensions: 0.31 L x 0.78 W x 0.43 H inches




END CAP IP40/IP65

Part #: Flex-O-EC40/65

Dimensions: 0.31 L x 0.78 W x 0.43 H inches

Note: IP67 Connector ships factory assembled with corresponding end cap. Customer may elect to cut and use IP40/67 end cap in the field, but installed assumes all responsibility for correct waterproofing and does not fall under factory warranty.

MOUNTING



AC ALUMINUM CHANNEL

Part # 3-Flex-O-AC

Length: 3ft



RCLIP ROTARY CLIP (not include)



Part # Flex-O-RClip




SA SADDLE CLIP

Part # Flex-O-SC (10/pk)


CHARACTERISTICS




4000K, 20°




4000K, 30°



4000K, 45°



4000K, 60°




AVERAGE BEAM ANGLE (50%): 35.0 DEG

4000K, 20°*45°

LEDSCAPE INDOOR & OUTDOOR POWER SUPPLY

LEDscape Constant Voltage Class 2 LED Drivers are available in indoor (IP50) and outdoor (IP68) enclosures. The outdoor enclosure is cETLus style with a built-in junction box on both the input and the output, and is suitable for all locations. With universal input voltage ranging from 120 to 277VAC, this series of drivers is designed for commercial, industrial and residential applications. Our 5in1 smooth flicker-free linear dimming down to 1% works with a wide variety of compatible dimmers, including 0-10V, Magnetic and Low voltage.



PRODUCT HIGHLIGHTS

	INDOOR	OUTDOOR
INPUT VOLTAGE	120/277 V	120/277 V
OUTPUT VOLTAGE	24V	Variable 18–25V
INPUT FREQUENCY	50/60 HZ	50/60 HZ
OPERATING TEMP	-13°F – 104°F	-13°F – 104°F
DEGREE OF PROTECTION (IP)	IP50	IP68
DIMMABLE	to 1%	to 1%
CLASS 2	up to 96W	All sizes
LOAD REQUIREMENTS	10%	10%

CHARACTERISTICS


INDOOR

Power	Output Current	Efficiency	Power Factor	Dimensions
18W	350mA	> 86%	>0.95	4.92" L X 2.09" W X 0.57"H
24W	2600mA	> 86%	>0.95	4.92" L X 2.09" W X 0.57"H
36W	4800mA	> 86%	>0.95	5.7" L X 2.09" W X 0.65"H
60W	2600mA	> 86%	>0.95	5.7" L X 2.09" W X 0.65"H
96W	4800mA	> 86%	>0.95	7.28" L X 2.2" W X 0.74"H
150W	7500mA	> 86%	>0.93	8.98" L X 2.2" W X 0.85"H
200W	8200mA	> 86%	>0.93	8.98" L X 2.2" W X 0.85"H

OUTDOOR

Power	Output Current	Efficiency	Power Factor	Dimensions
30W	1250mA	> 86%	>0.95	7.50" L X 3.62" W X 1.65"H
60W	2600mA	> 86%	>0.95	7.50" L X 3.62" W X 1.65"H
96W	4800mA	> 86%	>0.95	8.50" L X 3.66" W X 1.65"H
120W (2x60W)	5000mA	> 86%	>0.93	10.15" L X 4.85" W X 1.65"H
192W (2x96W)	8000mA	> 86%	>0.93	10.15" L X 4.85" W X 1.65"H
288W (3x96W)	9000mA	> 86%	>0.93	12.44" L X 4.85" W X 1.65"H
384W (4x96W)	16000mA	> 86%	>0.93	12.44" L X 4.85" W X 1.65"H

POWER AND CONNECTION DIAGRAM



POWER SUPPLY = Product Wattage X Length

24 Nominal supply voltage of LEDscape in Volt
Recommended MAC output of power supply 80%

To calculate MAX run distance from Power Supply to LED reference power drop chart : [Here](#).

Note: If using outdoor, verify contractor use included water and moisture tight enclosure. Not direct burial rated.

ORDERING CHART

NOTE: View additional options [here](#).

Ordering Example: PS-24-I-D3-60-U OR PS-24-O-D3-60-U

Series		Output Voltage		Environment		Dimming		Wattage OR				Voltage Input	
PS	Power supply	24	24V	I	Indoor (damp listed)	ND	Non Dimming	Indoor (I)		Outdoor (O)		U	120/277V
				O	Outdoor IP68	D3	5 in 1 Dimming	18	8W	30	30W		
				Indoor: IP50, damp listed. Class 2 up to 96W. Outdoor: IP68, cETLus enclosure with built-in junction box on input and output. Class 2 all sizes.				24	24W	60	60W		
								36	36W	96	96W		
								60	60W	120	120W		
								96	96W	192	192W		
								150	150W	288	288W		
								200	200W	384	384W		
								CU Custom Output		CU Custom Output			

DISCLAIMER: The information on these pages are as accurate as possible, however LEDscape or any reseller of LEDscape cannot be held liable for any damages resulting from errors or outdated information. LEDscape reserves the right to modify the information without informing the customers. Check for the latest version on the Internet, the most up to date information will be published on www.ledscape.com. Qualified and Licensed Electrical Contractor must install the product. This product should not be used in applications, devices or systems where incorrect operation of the product may result in personal injury (includes emergency lighting) without written permission from LEDscape. If nevertheless used in such applications, devices or systems LEDscape cannot be held liable for any resulting injury.