


LEDSCAPE FLEX NEON MULTI BEND IP67

LEDscape LED NEON Multi Bend by LED strip (IP67) is a high quality, flexible LED strips with a unique, diffuse co-extrusion technology that allows horizontal and vertical bending. The combination of high quality and exceptional flexibility, allows for an endless range of indoor and outdoor applications. The LEDscape offers a pre-assembled mirror welded connector for instant waterproof IP67 usage.

PRODUCT HIGHLIGHTS

- BINNING:** $\pm 50K$
- CRI:** 90
- EXPECTED LIFETIME:** L70 > 50,000 hours
- OPERATING TEMP:** 22°F – 131°F (–30°C – 55°C)
- DEGREE OF PROTECTION:** IP67
- RATING:** UL
- OUTPUT:** 286 lm/ft (large), 162lm/ft (small)
- RADIUS RADIUS:** 5.9 in
- CORD LENGTH EXPECTED:** 3 ft
- OPERATING VOLTAGE:** 24V, constant voltage
- WARRANTY:** 5 year
- FEATURES:** Dimmable, Plug & Play, Assorted colors, Accessories available, Effective heat dissipation, Excellent lumen/watt ratio, very flexible, custom output, custom colors.

CHARACTERISTICS

Power	Dimensions	Length Inc. ¹	Max Run Length ²	Dimming
LARGE 4.27 w/ft	0.79 x 0.79	Free Cut (any location)	16.4 ft	Low Voltage/ 0-10V
SMALL 2.44 w/ft	0.39 x 0.39			



Notes:

1. **Length Increments:** Refers to the Strip's cuttable segments. Example: If 1ft Power (P), you will cut 9.84 in or 14.76 in.
2. **Max Run Length:** Refers to the Strip's total run length from connector to end, including interconnected lengths. Example: if you are ordering 60 ft of Power, you will need 4 EA 16 ft lengths.

MAX. connection length between -4°F and -22°F is 1/3 of listed above. Lumen calculated at 2700K, please request individual data sheets if needed. Circuits with LEDscape product must have surge protection to qualify for 5 year warranty. LEDscape reserves the right to modify the information above without notice.

AVAILABLE COLORS

- Extra Warm White 2700K
- Warm White 3000K
- Cool White 3500K
- Natural White 4000K
- Cold White 5000K
- Custom



ORDERING CHART


Example: 20 -FLEX-NM-L-30-S67-AB

Length	LED Stock Code	Series		Color		Connector & Environment		Mounting	
16 ft NOTE: Refer to Max Run lengths. If total exceeds, you will receive multiple pieces. Example: 32 ft = (2) 16 ft	FLEX LED Strip (Outdoor IP67)	NM-L	120° Multi Bend LARGE	27	2700K	S67	Straight feed IP67	SC	Mounting Bracket
		NM-S	120° Multi Bending SMALL	30	3000K	B67	Bottom feed IP67	BC	Bendable Channel
				35	3500K	SA67	Side feed IP67	AC	Aluminum Channel
				40	4000K				
				50	5000K				
				CU	Custom Color				

Notes:

Product sold PER FOOT. Ships with factory IP67 Connection and end cap. Stock code may differ from UL/ETL certification, consult factory if required.

FLEX NEON LED CONNECTORS & MOUNTING



S67 STRAIGHT CONNECTOR SET IP67

Part #: Flex-NM-L-Conn-S67 (large)

Part #: Flex-T-NM-S-Conn-S67 (small)

Cord length: 3 ft

Dimensions: 0.12 L x 0.80 W x 0.80 inch (large)

0.12 L x 0.45 W x 0.45H inch (small)



SA67 SIDE CONNECTOR SET IP67

Part #: Flex-NM-L-Conn-SA67 (large)

Part #: Flex-T-NM-S-Conn-SA67 (small)

Cord length: 3 ft

Dimensions: 0.12 L x 0.80 W x 0.80 inch (large)

0.12 L x 0.45 W x 0.45H inch (small)




BA67 BOTTOM CONNECTOR SET IP67

Part #: Flex-NM-L-Conn-B67 (large)

Part #: Flex-NM-S-Conn-B67 (small)

Dimensions: 0.12 L x 0.80 W x 0.80 inch (large)

0.12 L x 0.45 W x 0.45H inch (small)



EC67 END CAP IP67

Part #: Flex-NM-L-Conn-EC67 (large)

Part #: Flex-NM-S-Conn-EC67 (small)

Dimensions: 0.12 L x 0.80 W x 0.80 inch (large)

0.12 L x 0.45 W x 0.45H inch (small)




EC40/67 END CAP IP40 & IP67

Part #: Flex-T-NM-L-EC40/67 (large)

Part #: Flex-T-NM-S-EC40/67 (small)

Dimensions: 0.15 L x 0.90 W x 0.90 inch (large)

0.12 L x 0.55 W x 0.55H inch (small)



JMP68 JUMPER IP68

Part #: Flex-NM-L-JMP68XX (large)

Part #: Flex-NM-S-JMP68XX (small)

Length: XX (inches, customer to specify)

Dimensions: 0.12 L x 0.80 W x 0.80 inch (large)

0.12 L x 0.45 W x 0.45H inch (small)


Note: IP67 Connector ships factory assembled with corresponding end cap. Customer may elect to cut and use IP40/65 end cap in the field, but installed assumes all responsibility for correct waterproofing and does not fall under factory warranty.

NEON LED MOUNTING

AC ALUMINUM CHANNEL (LARGE)

Part # 3-Flex-NM-L-AC


Length: 3 ft



AC ALUMINUM CHANNEL (SMALL)


Part # 3-Flex-NM-S-AC

Length: 3 ft




SC STAINLESS STEEL CLIP (LARGE)

Part # 3-Flex-NM-L-SC



SC STAINLESS STEEL CLIP (SMALL)


Part # 3-Flex-NM-S-SC



BC BENDABLE STAINLESS STEEL CHANNEL (LARGE)

Part # 3-Flex-NM-L-BC


Length: 3 ft



BC BENDABLE STAINLESS STEEL CHANNEL (SMALL)

Part # 3-Flex-NM-S-BC


Length: 3 ft



Channels provided in 3 FT segments. 6 FT segments available on request. MOQ applies

LEDSCAPE INDOOR & OUTDOOR POWER SUPPLY

LEDscape Constant Voltage Class 2 LED Drivers are available in indoor (IP50) and outdoor (IP68) enclosures. The outdoor enclosure is cETLus style with a built-in junction box on both the input and the output, and is suitable for all locations. With universal input voltage ranging from 120 to 277VAC, this series of drivers is designed for commercial, industrial and residential applications. Our 5in1 smooth flicker-free linear dimming down to 1% works with a wide variety of compatible dimmers, including 0-10V, Magnetic and Low voltage.



PRODUCT HIGHLIGHTS

	INDOOR	OUTDOOR
INPUT VOLTAGE	120/277 V	120/277 V
OUTPUT VOLTAGE	24V	Variable 18–25V
INPUT FREQUENCY	50/60 HZ	50/60 HZ
OPERATING TEMP	-13°F – 104°F	-13°F – 104°F
DEGREE OF PROTECTION (IP)	IP50	IP68
DIMMABLE	to 1%	to 1%
CLASS 2	up to 96W	All sizes
LOAD REQUIREMENTS	10%	10%

CHARACTERISTICS


INDOOR

Power	Output Current	Efficiency	Power Factor	Dimensions
18W	350mA	> 86%	>0.95	4.92" L X 2.09" W X 0.57"H
24W	2600mA	> 86%	>0.95	4.92" L X 2.09" W X 0.57"H
36W	4800mA	> 86%	>0.95	5.7" L X 2.09" W X 0.65"H
60W	2600mA	> 86%	>0.95	5.7" L X 2.09" W X 0.65"H
96W	4800mA	> 86%	>0.95	7.28" L X 2.2" W X 0.74"H
150W	7500mA	> 86%	>0.93	8.98" L X 2.2" W X 0.85"H
200W	8200mA	> 86%	>0.93	8.98" L X 2.2" W X 0.85"H

OUTDOOR

Power	Output Current	Efficiency	Power Factor	Dimensions
30W	1250mA	> 86%	>0.95	7.50" L X 3.62" W X 1.65"H
60W	2600mA	> 86%	>0.95	7.50" L X 3.62" W X 1.65"H
96W	4800mA	> 86%	>0.95	8.50" L X 3.66" W X 1.65"H
120W (2x60W)	5000mA	> 86%	>0.93	10.15" L X 4.85" W X 1.65"H
192W (2x96W)	8000mA	> 86%	>0.93	10.15" L X 4.85" W X 1.65"H
288W (3x96W)	9000mA	> 86%	>0.93	12.44" L X 4.85" W X 1.65"H
384W (4x96W)	16000mA	> 86%	>0.93	12.44" L X 4.85" W X 1.65"H

POWER AND CONNECTION DIAGRAM



POWER SUPPLY = Product Wattage X Length

24 Nominal supply voltage of LEDscape in Volt
Recommended MAC output of power supply 80%

To calculate MAX run distance from Power Supply to LED reference power drop chart : [Here](#).

ORDERING CHART

Ordering Example: PS-24-I-D3-60-U OR PS-24-O-D3-60-U

Series		Output Voltage		Environment		Dimming		Wattage OR				Voltage Input	
PS	Power supply	24	24V	I	Indoor (damp listed)	ND	Non Dimming	Indoor (I)		Outdoor (O)		U	120/277V
				O	Outdoor IP68	D3	5 in 1 Dimming	18	8W	30	30W		
				Indoor: IP50, damp listed. Class 2 up to 96W. Outdoor: IP68, cETLus enclosure with built-in junction box on input and output. Class 2 all sizes.				24	24W	60	60W		
								36	36W	96	96W		
								60	60W	120	120W		
								96	96W	192	192W		
								150	150W	288	288W		
								200	200W	384	384W		
								CU Custom Output		CU Custom Output			

DISCLAIMER: The information on these pages are as accurate as possible, however LEDscape or any reseller of LEDscape cannot be held liable for any damages resulting from errors or outdated information. LEDscape reserves the right to modify the information without informing the customers. Check for the latest version on the Internet, the most up to date information will be published on www.ledscape.com. Qualified and Licensed Electrical Contractor must install the product. This product should not be used in applications, devices or systems where incorrect operation of the product may result in personal injury (Includes emergency lighting) without written permission from LEDscape. If nevertheless used in such applications, devices or systems LEDscape cannot be held liable for any resulting injury.